(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织 国际局

(43) 国际公布日

2006年5月18日(18.05.2006)



(10) 国际公布号 WO 2006/050637 A1

(51) 国际专利分类号7:

B60L 11/00, 11/18

(21) 国际申请号:

PCT/CN2004/001373

(22) 国际申请日:

2004年11月29日(29.11.2004)

(25) 申请语言:

中文

(26) 公布语言:

中文

(30) 优先权: 200410090796.0

2004年11月11日(11.11.2004)

(71) 申请人 (对除美国外的所有指定国): 北京电巴科技 有限公司(BELJING DIANBA TECHNOLOGY CO. LTD) [CN/CN]; 中国北京市海淀区学清路16号学知 轩2008室, Beijing 100083 (CN)。


- (75) 发明人/申请人 (仅对美国): 李钢(LI, Gang)

[CN/CN]; 中国甘肃省兰州市南昌路872号, Gansu 730000 (CN).

- (74) 代理人:北京安信方达知识产权代理有限公司 (AFD CHINA INTELLECTUAL PROPERTY LAW OFFICE); 中国北京市海淀区学清路8号科技财富 中心B座三层305A, Beijing 100085 (CN)。
- (81) 指定国 (除另有指明,要求每一种可提供的国家保 ₺): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) 拊定国 (除另有捐明,要求每一种可提供的地区 保护): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA,

(见埃页)

- (54) Title: AN ELECTRICAL BUS SYSTEM
- (54) 发明名称: 一种电动公交系统



- ELECTRICAL BUS EYBTEM
 CONTROL UNI
 CARD-TYPE ACCUMULATOR BET ELECTRICAL BUS
 CARD-TYPE ACCUMULATOR SET DISASSEMELY MEANS

(57) Abstract: An electrical bus system includes a bus mounted a card-type accumulator set and vehicle-mounted control system, a charging station arranged at fired point and a disassembly means of card-type accumulator set, when the electrisystem, a charging station arranged at fired point and a disassembly means of card-type accumulator set, when the electrical bus need change the card-type accumulator set, the disassembly means takes down the card-type accumulator set of the electrical bus and put the charged accumulator set to the electrical bus. Each of the charging station and the disassembly has control system wherein the control system of the disassembly means, the control system of the vehicle-mounted control system and the control system of the charging station system can communicate with each other. The invention fully uses the power between the peak and low of the grid to charge the accumulator set, so it can protect the environment and save energy, rapidly and truly operate the assemble and disassemble of the accumulator for insuring the electrical bus continually on the line to greatly improve the utilize ratio of the electric bus.

[见练页]